



portata S.W.L. kg	sbraccio S span m	H totale height m	h sotto- trave under beam mm	codice colonna code column	h1 mm	A mm	B mm	C mm	D mm	□ P mm	T mm	peso kg
250	2	3	2805	S0230A20	2435	250	600	570	170	350	160	178
	3	3	2765	S0230A30	2395	250	600	630	170	350	200	213
	4	3	2725	S0230B40	2355	250	600	630	170	350	240	287
	5	3	2725	S0230C50	2355	300	750	755	170	450	240	377
	6	3	2665	S0230E60	2295	400	850	820	170	600	300	641
	7	3	2680	S0230L70	2295	450	880	850	170	800	300	820
	8	3	2680	S0230L80	2295	450	880	850	170	800	300	900
500	2	3	2765	S0530B20	2335	250	600	570	170	350	200	209
	3	3	2725	S0530C30	2295	300	750	680	170	450	240	312
	4	3	2695	S0530E40	2265	400	850	690	170	600	270	536
	5	3	2665	S0530E50	2235	400	850	760	170	600	300	600
	6	3	2680	S0530L60	2195	450	850	885	170	800	330	815
	7	3	2650	S0530L70	2100	450	980	950	170	800	330	895
	8	3	2620	S0530L80	2100	450	980	950	170	800	360	998
1000	2	3	2695	S1030E20	2190	400	850	635	175	600	270	462
	3	3	2665	S1030E30	2160	400	850	690	175	600	300	515
	4	3	2680	S1030L40	2120	450	880	755	175	800	300	717
	5	3	2650	S1030L50	2090	450	880	830	175	800	330	806
	6	3	2620	S1030L60	2040	450	880	940	175	800	360	1156
	7	3	2580	S1030L70	2040	500	980	940	175	900	400	1450
	8	3	2530	S1030L80	2000	500	980	960	175	900	400	1560
2000	2	3	2625	S2030L20	2005	450	880	830	175	800	300	620
	3	3	2620	S2030L30	1975	450	880	940	175	800	330	691
	4	3	2580	S2030L40	1925	500	980	940	175	900	360	1023
	5	3	2530	S2030L50	1875	500	980	940	175	900	400	1167

\* Tutti i dati in tabella sono indicativi e non impegnativi