



PORTATA	kg	1.000	1.500	2.000	3.000	5.000	10.000	
CARRELLO	tipo	CS010	CS015	CS020	CS030	CS050	CS100	
raggio minimo curvatura	m	1	1	1,1	1,3	1,4	2	
A	mm	246	261	275	333	377	423	
B	mm	81	88	94	115	126	155	
C	mm	125	132	141	167	192	190	
D	mm	27	31	37	39	49	71	
E	mm	15	17	20	23	31	50	
F	mm	8	10	12	14	16	20	
G	tirante A	mm	240	247	270	295	-	-
	tirante B	mm	311	309	327	343	354	387
	tirante C	mm	413	412	429	-	456	489
H	mm	22	22	26	28	38	48	
L	mm	8	8	10	12	16	30	
N	mm	19	21	23	26	35	42	
O	mm	37	37	36	38	41	42	
P	mm	68	74	79	99	109	135	
Q	mm	95	102	108	130	144	176	
R	mm	220	235	260	310	350	396	
S	mm	120	125	132	155	167	200	
U	mm	97	101	109	129	142	158	
V	mm	51	55	64	72	84	105	
tirante A	ala trave	mm	58-131	70-135	80-143	90-150	-	-
tirante B		mm	58-200	70-200	80-200	90-200	106-200	120-200
tirante C		mm	58-300	70-300	80-300	90-300	106-300	120-300
peso carrello	kg	11	13	18	29	42	77	